



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Elektrolyt 1524 1000 and 1524 2000**

Revision date: 27.12.2020

Product code: 1524x000

Page 1 of 7

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Elektrolyt 1524 1000 and 1524 2000

#### Further trade names

1524 1000 Elektrolyt 2 l

1524 2000 Elektrolyt 10 l

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

For polishing chrome-cobalt alloys. Solution is ready for use.

#### Uses advised against

No information available.

### 1.3. Details of the supplier of the safety data sheet

Company name: Renfert GmbH  
Street: Untere Giesswiesen 2  
Place: D-78247 Hilzingen  
Telephone: +49 7731 8208-0  
e-mail: info@renfert.com  
Contact person: Frau Andris  
e-mail: silke.andris@renfert.com  
Internet: www.renfert.com

Telefax: +49 7731 8208-70

### 1.4. Emergency telephone number:

GB: 0044 151 951 3317 (Health and Safety Executive (HSE) Chemicals) | USA: 800-222-1222 (National Poison Control number) | CA: British Columbia: 800-567-8911 or 604-682-5050 Alberta: 1-800-332-1414 or 944-1414 Saskatchewan: 1-866-454-1212 Manitoba: 1-855-776-4766 Ontario: 1-800-268-9017 Quebec: 1-800-463-5060 New Brunswick: 911 Newfoundland: 1-866-727-1110 Northwest Territories: 1-800-332-1414 Nova Scotia: 1-800-565-8161 | AU: 13 11 26 | ZA: 021 938 6084 (Office Hours) or 021 931 6129 (24 Hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Harmful if swallowed.

Causes skin irritation.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

ethane-1,2-diol

Signal word:

Warning

Pictograms:



##### Hazard statements

H302

Harmful if swallowed.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H373

May cause damage to kidneys through prolonged or repeated exposure by swallowing.

##### Precautionary statements

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P337+P313

If eye irritation persists: Get medical advice/attention.

P314

Get medical advice/attention if you feel unwell.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Elektrolyt 1524 1000 and 1524 2000**

Revision date: 27.12.2020

Product code: 1524x000

Page 2 of 7

## 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Electrolyte solution

#### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
107-21-1	ethane-1,2-diol			> 80%
	203-473-3		01-2119456816-28	
	Acute Tox. 4, STOT RE 2; H302 H373			
7664-93-9	Sulphuric acid			< 15%
	231-639-5	016-020-00-8	01-2119458838-20	
	Skin Corr. 1A; H314			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Take off contaminated clothing and wash it before reuse.

Symptoms of poisoning may develop several hours following exposure. Victim should be under medical observation for at least 48 hours after exposure.

#### After inhalation

Provide fresh air.

In case of respiratory tract irritation, consult a physician.

#### After contact with skin

IF ON SKIN: Wash with plenty of soap and water.

In case of skin irritation, consult a physician.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

When in doubt or if symptoms are observed, get medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water, Dry extinguishing powder, Foam, Carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Sulphur oxides, Carbon monoxide

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes and skin.

Use personal protection equipment.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Elektrolyt 1524 1000 and 1524 2000**

Revision date: 27.12.2020

Product code: 1524x000

Page 3 of 7

Provide adequate ventilation.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Handle and open container with care.

Avoid contact with eyes and skin. Use personal protection equipment.

When using do not eat, drink or smoke.

**Advice on protection against fire and explosion**

No special fire protection measures are necessary.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep/Store only in original container.

Keep container tightly closed in a cool, well-ventilated place.

**Hints on joint storage**

Do not store together with: Alkali (lye)

**Further information on storage conditions**

Protect against: Humidity

**7.3. Specific end use(s)**Please refer to our internet website for more information: [www.renfert.com](http://www.renfert.com)**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL
7664-93-9	Sulphuric acid (mist)	-	0.05		TWA (8 h)	WEL

**8.2. Exposure controls****Appropriate engineering controls**

Safe handling: see section 7

**Protective and hygiene measures**

Avoid contact with skin, eyes and clothes.

Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

**Eye/face protection**

Wear eye/face protection.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber), FKM (fluoro rubber)

Thickness of the glove material: mind. 0,5 mm

Breakthrough time: &gt; 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

**Skin protection**

Wear suitable protective clothing.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Elektrolyt 1524 1000 and 1524 2000**

Revision date: 27.12.2020

Product code: 1524x000

Page 4 of 7

**Respiratory protection**

Use only in well-ventilated areas.  
Usually no personal respirative protection necessary.  
Respiratory protection necessary at: aerosol or mist formation

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Liquid  
Colour: colourless  
Odour: odourless  
pH-Value (at 20 °C): 1

**Changes in the physical state**

Melting point: not determined  
Initial boiling point and boiling range: 197 °C  
Flash point: > 100 °C

**Flammability**

Solid: not applicable  
Gas: not applicable

**Explosive properties**

not explosive according to EU A.14

Lower explosion limits: 3,2 vol. %  
Upper explosion limits: 15,3 vol. %  
Ignition temperature: 410 °C

**Auto-ignition temperature**

Solid: not applicable  
Gas: not applicable

Decomposition temperature: not determined

Vapour pressure: < 1 hPa  
(at 20 °C)Density (at 20 °C): 1,19 - 1,22 g/cm<sup>3</sup>

Water solubility: miscible

Partition coefficient: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: not determined

Evaporation rate: not determined

**9.2. Other information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

Violent reaction with: Alkali (lye)  
Reactions with metals, with evolution of hydrogen.

**10.4. Conditions to avoid**

No special measures are necessary.

**10.5. Incompatible materials**

Violent reaction with: Alkali (lye)

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Elektrolyt 1524 1000 and 1524 2000**

Revision date: 27.12.2020

Product code: 1524x000

Page 5 of 7

**Acute toxicity**

Harmful if swallowed.

**ATEmix calculated**

ATE (oral) 579,4 mg/kg

CAS No	Chemical name	Exposure route	Dose	Species	Source	Method
107-21-1	ethane-1,2-diol	oral	LD50 mg/kg	7712	Rat	IUCLID

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (ethane-1,2-diol)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Further information**

The product has not been tested. The statement is derived from the properties of the single components.

**SECTION 12: Ecological information****12.1. Toxicity**

There are no data available on the mixture itself.

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
107-21-1	ethane-1,2-diol	-1,36

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No information available.

**Further information**

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Send to a hazardous waste incinerator facility under observation of official regulations.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**List of Wastes Code - residues/unused products**

060101 WASTES FROM INORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of acids; sulphuric acid and sulphurous acid; hazardous waste

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Elektrolyt 1524 1000 and 1524 2000**

Revision date: 27.12.2020

Product code: 1524x000

Page 6 of 7

**14.1. UN number:** UN 2796  
**14.2. UN proper shipping name:** SULPHURIC ACID with not more than 51 % acid  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8

**Marine transport (IMDG)**

**14.1. UN number:** UN 2796  
**14.2. UN proper shipping name:** SULPHURIC ACID with not more than 51 % acid  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8



Marine pollutant: no

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 2796  
**14.2. UN proper shipping name:** SULPHURIC ACID with not more than 51 % acid  
**14.3. Transport hazard class(es):** 8  
**14.4. Packing group:** II  
Hazard label: 8

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Further information: see section 6, 7, 8

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3: Flüssige Stoffe oder Gemische, die Kriterien für eine der folgenden in Anhang I der Verordnung (EG) 2004/42/EC (VOC): not applicable

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D):

1 - slightly hazardous to water

**Additional information**

REGULATION (EC) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on substances that deplete the ozone layer: not applicable

REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic pollutants

: not applicable

REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of hazardous chemicals: not applicable



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Elektrolyt 1524 1000 and 1524 2000**

Revision date: 27.12.2020

Product code: 1524x000

Page 7 of 7

## SECTION 16: Other information

### Changes

Abs. 11, 12, 15, 16 \* Data changed compared with the previous version

### Abbreviations and acronyms

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LD50: lethal dose, 50%

ATE: Acute Toxicity Estimates

LC50: lethal concentration, 50%

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT RE 2; H373	Calculation method

### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to kidneys through prolonged or repeated exposure by swallowing.
H373	May cause damage to organs through prolonged or repeated exposure.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Restricted to professional users.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*